

Communication interface GWD3

Presentation



The GWD3 communication interface is intended for connection of Seltron controllers, room units and thermostats to the SeltronHome platform.

Typical application

- GWD3 communication interface is used to transfer data between SELTRON devices and the SeltronHome platform, thus enabling remote control and management of the system.
- The connection with internet can be wired using Ethernet cable (UTP) or wireless using Wi-Fi network.



Features


- Connection of up to two Seltron controllers.
- Enables automatic software update of the WGD module (OTA).
- LED indicating input and output statuses.
- Easy and automatic connection with a Wi-Fi network, using WPS quick connection button.
- Simple wall installation with two supplied screws and easy connection to the Seltron controller using two-wire cable.
- It enables remote management, the configuration and servicing of the device from anywhere and anytime.

Description



- 1 - Connection with Seltronhome platform.
- 2 - Connection with a Wi-Fi network.
- 3 - Ethernet connection.
- 4 - First controller.
- 5 - Second controller.
- 6 - Power supply.
- 7 - WPS/Reset button.
- 8 - Registration key.
- 9 - Ethernet connection.

Technical characteristics	GWD3
LED indication of connected Seltron controllers	•
LED indication of connection with local network (LAN or Wi-Fi)	•
LED indication of connection with SeltronHome platform	•
Button for setup of communication interface and WPS	•
Setup and installation	
Possibility of wall installation	•
Simple installation and connection	•
Supported Seltron controllers	
Series WDC - v3.1.0 and newer	•
Series KXD - v1.0.0 and newer	•
Series WXD - v2.0.1 and newer	•
Series SGC - v4.0.0 and newer	•
Series KUD - 1.2.2 and newer	•
Series KPD - v1.3.0 and newer	•
Series AHD - v1.0.0 and newer	•
Series AHC - v1.0.1 and newer	•
Series CMP - v3.2.0 and newer	•
Series BXD L - v2.1.0 and newer	•
Technical specifications	
Connection voltage	230 V~, 50 Hz
Energy consumption	0,5 W
Data usage during communication with platform	-30 MB/device/month
Method of installation	On the wall
Degree of protection	IP20 to EN 60529
Safety class	II to EN 60730-1
Cross-section of network cables	0,5÷0,75 mm ²
Cross-section of communication cables	0,25÷0,33 mm ²
Permitted relative humidity	max. 85 % RH at 25 °C
Housing material	PC-thermoplastic
Permitted ambient temperature	5÷40 °C
Storage temperature	-20÷65 °C
Wireless connection	Wi-Fi IEEE 802.11b/g/n, 2,4 GB
Program class	A
Product weight	465 g
Nr. of pieces in packing unit	24 pcs
Dimensions	
Electrical connection	

Item	Order code	Description
 A black rectangular communication module with the SELTRON logo at the top, a vertical row of four green LEDs in the center, and the model number GWD3 at the bottom.	1GWD3-040	Communication module SELTRON GWD3

Seltron d.o.o.
Tržaška cesta 85 A
SI-2000 Maribor
Slovenia

T: +386 (0)2 671 96 00
F: +386 (0)2 671 96 66
sales@seltron.eu
www.seltron.eu